BASIX[°]Certificate

Building Sustainability Index www.basix.nsw.gov.au

Single Dwelling

Certificate number: 1779431S

This certificate confirms that the proposed development will meet the NSW government's requirements for sustainability, if it is built in accordance with the commitments set out below. Terms used in this certificate, or in the commitments, have the meaning given by the document entitled "BASIX Definitions" dated 10/09/2020 published by the Department. This document is available at www.basix.nsw.gov.au

Secretary

Date of issue: Wednesday, 08 January 2025

To be valid, this certificate must be submitted with a development application or lodged with a complying development certificate application within 3 months of the date of issue.



Project summary		
Project name	106 school lane - Existing Grann	iy Flat
Street address	106 SCHOOL Lane BUDGEE B	JDGEE 2850
Local Government Area	Mid-Western Regional Council	
Plan type and plan number	Deposited Plan DP755429	
Lot no.	264	
Section no.	-	
Project type	dwelling house (detached) - seco	ndary dwelling
No. of bedrooms	2	
Project score		
Water	✓ 36	Target 30
Thermal Performance	V Pass	Target Pass
Energy	71	Target 59
Materials	-50	Target n/a

Certificate Prepared by

Name / Company Name: Play Design Studio

ABN (if applicable): 91135261237

Version: 4.03 / EUCALYPTUS_03_01_0 Certificate No.: 1779431S Wednesday, 08 January 2025

Description of project

Project address

Project name	106 school lane - Existing Granny Flat
Street address	106 SCHOOL Lane BUDGEE BUDGEE 2850
Local Government Area	Mid-Western Regional Council
Plan type and plan number	Deposited Plan DP755429
Lot no.	264
Section no.	-
Project type	
Project type	dwelling house (detached) - secondary dwelling
No. of bedrooms	2
Site details	
Site area (m²)	62200
Roof area (m ²)	98
Conditioned floor area (m ²)	53.0
Unconditioned floor area (m ²)	5.0
Total area of garden and lawn (m ²)	200
Roof area of the existing dwelling (m ²)	150
Number of bedrooms in the existing dwelling	3

Assessor details and thermal loads Assessor number n/a Certificate number n/a Climate zone n/a Area adjusted cooling load (MJ/ n/a m².year) Area adjusted heating load (MJ/ n/a m².year) **Project score** Water **V** 36 Target 30 Thermal Performance 4 Pass Target Pass Energy 71 Target 59 Materials -50 Target n/a

Schedule of BASIX commitments

The commitments set out below regulate how the proposed development is to be carried out. It is a condition of any development consent granted, or complying development certificate issued, for the proposed development, that BASIX commitments be complied with.

Water Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Fixtures			
The applicant must install showerheads with a minimum rating of 4 star (> 4.5 but <= 6 L/min plus spray force and/or coverage tests) in all showers in the development.		~	~
The applicant must install a toilet flushing system with a minimum rating of 5 star in each toilet in the development.		~	~
The applicant must install taps with a minimum rating of 5 star in the kitchen in the development.		~	
The applicant must install basin taps with a minimum rating of 5 star in each bathroom in the development.		~	
Alternative water			
Rainwater tank			
The applicant must install a rainwater tank of at least 5000 litres on the site. This rainwater tank must meet, and be installed in accordance with, the requirements of all applicable regulatory authorities.	~	~	~
The applicant must configure the rainwater tank to collect rain runoff from at least 98 square metres of the roof area of the development (excluding the area of the roof which drains to any stormwater tank or private dam).		~	~
The applicant must connect the rainwater tank to:			
all toilets in the development		 	 ✓
 the cold water tap that supplies each clothes washer in the development 		 	 ✓
 at least one outdoor tap in the development (Note: NSW Health does not recommend that rainwater be used for human consumption in areas with potable water supply.) 		Y	· · ·

Thermal Performance and Materials commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Do-it-yourself Method	-	'	
General features			
The dwelling must be a Class 1 dwelling according to the National Construction Code, and must not have more than 2 storeys.	~	~	~
The conditioned floor area of the dwelling must not exceed 300 square metres.	~	~	~
The dwelling must not contain open mezzanine area exceeding 25 square metres.	~	~	~
The dwelling must not contain third level habitable attic room.	~	~	~
Floor, walls and ceiling/roof	•		
The applicant must construct the floor(s), walls, and ceiling/roof of the dwelling in accordance with the specifications listed in the table below.	~	~	~
The applicant must adopt one of the options listed in the tables below to address thermal bridging in metal framed floor(s), walls and ceiling/roof of the dwelling.	~	~	~
The applicant must show through receipts that the materials purchased for construction are consistent with the specifications listed in the tables below.			-

Construction	Area - m²	Additional insulation required	Options to address thermal bridging	Other specifications
floor - concrete slab on ground, waffle pod slab.	58	nil;not specified	nil	
external wall: framed (fibre cement sheet or boards); frame: timber - hardwood predominant incl. glue laminated beams.	all external walls	3.00 (or 3.50 including construction);fibreglass batts or roll + reflective foil in the cavity	nil	wall colour: Medium (solar absorptance 0.48-0.7)
internal wall: plasterboard; frame: timber - hardwood predominant incl. glue laminated beams.	80	fibreglass batts or roll	nil	

Const	ruction	Area - m²	Additional insulation required	Options to address thermal bridging	Other specifications
pitche timber	and roof - flat ceiling / d roof, framed - metal roof, - hardwood predominant ue laminated beams.	98	ceiling: 6.1 (up), roof: foil/ sarking ;ceiling: not specified; roof: not specified.	nil	roof space ventilation: unventilated; roof colour: medium (solar absorptance 0.48-0.59); please select
		·			·
Note	 Insulation specified in this 	Certificate must be installed in accor	dance with the ABCB Housing Provisio	ns (Part 13.2.2) of the National Constr	uction Code.
Note	• If the additional ceiling ins	ulation listed in the table above is gre	eater than R3.0, refer to the ABCB Hous	sing Provisions (Part 13.2.3 (6)) of the	National Construction Code.
Note • In some climate zones, insulation should be installed with due consideration of condensation and associated interaction with adjoining building materials.					
Note	Roof space ventilation nee	eds to meet the condensation manag	ement provisions in the ABCB Housing	Provisions of the National Construction	n Code.
Note	Thermal breaks must be in	nstalled in metal framed walls and ap	plicable roofs in accordance with the Al	BCB Housing Provisions of the Nation	al Construction Code.

Thermal Performance and Materials commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Ceiling fans			-
The applicant must install at least one ceiling fan in at least one daytime habitable space, such as living room.	~	~	~
The applicant must install at least one ceiling fan in each bedroom.	~	~	~
• The minimum number and diameter of ceiling fans in a daytime habitable space must be installed in accordance with the ABCB Housing Provisions (Part 13.5.2) of the National Construction Code .	~	~	~

Thermal Performance and Materials commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check			
Glazed windows, doors and skylights						
The applicant must install the windows, glazed doors and shading devices described in the table below, in accordance with the specifications listed in the table. Relevant overshadowing specifications must be satisfied for each glazed window and door.	~	~	~			
The dwelling may have 1 skylight (<0.7 square metres) which is not listed in the table.	~	~	~			
The following requirements must also be satisfied in relation to each window and glazed door:	~	~	~			
• The applicant must install windows and glazed doors in accordance with the height and width, frame and glazing types listed in the table.	~	~	~			
• Each window and glazed door must have a U- value no greater than that listed and a Solar Heat Gain Coefficient (SHGC) within the range listed. Total system U values and SHGC must be calculated in accordance with National Fenestration Rating Council (NFRC) conditions.		~	~			
The applicant must install the skylights described in the table below, in accordance with the specifications listed in the table. Total skylight area must not exceed 3 square metres (the 3 square metre limit does not include the optional additional skylight of less than 0.7 square metres that does not have to be listed in the table).	~	~	~			

Glazed window/door no.	Maximum height (mm)	Maximum width (mm)	Frame and glass specification	Shading device (Dimension within 10%)	Overshadowing				
North facing	North facing								
G1	1200.00	1200.00	aluminium, single glazed (U-value: <=6.5, SHGC: >0.74)	eave 450 mm, 300 mm above head of window or glazed door	not overshadowed				
East facing									
G2	1200.00	1200.00	aluminium, single glazed (U-value: <=6.5, SHGC: >0.74)	none	not overshadowed				
G3	1000.00	1500.00	aluminium, single glazed (U-value: <=6.5, SHGC: >0.74)	none	not overshadowed				
South facing	South facing								

BASIX Department of Planning, Housing and Infrastructure

page 7/11

Glazed window/door no.	Maximum height (mm)	Maximum width (mm)	Frame and glass specification	Shading device (Dimension within 10%)	Overshadowing
G4	2100.00	2100.00	aluminium, single glazed (U-value: <=6.5, SHGC: >0.74)	verandah 3000 mm, 300 mm above base of window or glazed door	not overshadowed
West facing					
G5	1000.00	1500.00	aluminium, single glazed (U-value: <=6.5, SHGC: >0.74)	none	not overshadowed
G6	900.00	600.00	aluminium, single glazed (U-value: <=6.5, SHGC: >0.74)	none	not overshadowed

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
Hot water		'	
The applicant must install the following hot water system in the development, or a system with a higher energy rating: gas instantaneous with a performance of 5 stars.	~	~	~
Cooling system			
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning - ducted; Energy rating: 5 star (cold zone)		~	~
The applicant must install the following cooling system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning - ducted; Energy rating: 5 star (cold zone)		`	~
Heating system			
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 living area: 1-phase airconditioning - ducted; Energy rating: 5 star (cold zone)		~	~
The applicant must install the following heating system, or a system with a higher energy rating, in at least 1 bedroom: 1-phase airconditioning - ducted; Energy rating: 5 star (cold zone)		~	~
Ventilation			-
The applicant must install the following exhaust systems in the development:			
At least 1 Bathroom: individual fan, ducted to façade or roof; Operation control: manual switch on/off		 	~
Kitchen: individual fan, ducted to façade or roof; Operation control: manual on / timer off		 	~
Laundry: natural ventilation only, or no laundry; Operation control: n/a		 Image: A set of the set of the	~
Artificial lighting			
The applicant must ensure that a minimum of 80% of light fixtures are fitted with fluorescent, compact fluorescent, or light-emitting- diode (LED) lamps.		~	~
Natural lighting			
The applicant must install a window and/or skylight in the kitchen of the dwelling for natural lighting.	~	`	~

Energy Commitments	Show on DA plans	Show on CC/CDC plans & specs	Certifier check
The applicant must install a window and/or skylight in 1 bathroom(s)/toilet(s) in the development for natural lighting.	~	>	~
Other			
The applicant must install a gas cooktop & electric oven in the kitchen of the dwelling.		~	
The applicant must install a fixed outdoor clothes drying line as part of the development.		~	

Legend

In these commitments, "applicant" means the person carrying out the development.

Commitments identified with a V in the "Show on DA plans" column must be shown on the plans accompanying the development application for the proposed development (if a development application is to be lodged for the proposed development).

Commitments identified with a V in the "Show on CC/CDC plans and specs" column must be shown in the plans and specifications accompanying the application for a construction certificate / complying development certificate for the proposed development.

Commitments identified with a V in the "Certifier check" column must be certified by a certifying authority as having been fulfilled, before a final occupation certificate (either interim or final) for the development may be issued.